

PRODUCT SPECIFICATIONS & TECHNICAL DATA

PETROFLO MOLY M-4 GREASE

PETROFLO MOLY M-4, is a high performance, multi-purpose lubricant. It is highly water resistant grease, and because of its inherent qualities, lasts longer than conventional grease. This unique feature results in reducing time spent in lubricating equipment. **PETROFLO MOLY M-4**, also has excellent reversibility, and because of its extensive operating range, permits minimizing inventory. The addition of Molybdenum Disulphide, plates the bearing surfaces against friction and wear, and thus, increases lubrication protection.

OUTSTANDING FEATURES:

- Resists water washouts;
- Resists high temperatures;
- Dark gray color identification;
- Fights friction wear;
- Withstands extreme pressure loads;
- Combats corrosion and rusting;
- Excellent adhesive and cohesive qualities.

TYPICAL ANALYSIS

Worked penetration	287
Penetration after 100 strokes	295
Aluminum complex % soap	10.5
Dropping point F.	500 min.
Reversibility	Excellent
Corrosion (D174)	PASS
Operating temp. range. F.	15-350
Color	Charcoal
Timken OK Load	50 lbs.
Moly content	1% min.

The above analyses are typical inspections only and the finished product may vary from batch to batch.