



OUR BUSINESS IS HEAVY DUTY LUBRICANTS

Tel: (305)681-6110 Fax: (305)681-0906 / Miami, FL 33167 www.PETRO-FLORIDA.com

PRODUCT SPECIFICATIONS & TECHNICAL DATA

Marine SAE 80W-90 High Viscosity Gear Lube

PETROFLO BRAND Marine SAE 80W-90 High Viscosity Gear Lube are special marine grade formulations designed to withstand high amounts of water contamination. It contains stable extreme pressure additives and corrosion inhibitors to protect gears and bearings against corrosion. Special antifoam agents insure excellent lubrication to all gears and bearings under the severe churning action of marine gear cases.

APPLICATION:

PETROFLO BRAND Marine SAE 80W-90 High Viscosity Gear Lube may be used in all outboard gear cases where an SAE 80W-90 API GL-4 gear lubricant or older Type C is specified. Older models (prior to 1978) sometimes require special products. Check your owner's manual for models over ten years old. Johnson and Evinrude models with electric shift (1972 and earlier) and pre-1977 OMC Stern Drive require ATF Automatic Transmission Fluid.

PETROFLO BRAND Marine SAE 80W-90 High Viscosity Gear Lube may be used in lower units calling for a marine grade SAE 80W-90 API GL-5 gear lubricant. It is also recommended for lower units that require a SAE 90 Hypoid gear oil.

BENEFITS:

- Meet and/or exceed requirements of API GL-5
- Outstanding gear and bearing protection
- Combats rust and corrosion
- Provides outstanding anti-foam and oil oxidation protection
- Compatible with other gear oils under a wide range of operating conditions

TYPICAL ANALYSIS

PETROFLO BRAND Marine SAE 80W-90 High Viscosity Gear Lube

| | |
|------------------------|------|
| Gravity API | 26.3 |
| Viscosity Index | 95 |
| Viscosity Cst @ 40° C | 150 |
| Viscosity Cst @ 100° C | 15 |

The above analyses are typical inspections only and the finished product may vary from batch to batch.