



Mobil Delvac 1300 Super

Mobil Commercial Vehicle Lube, United States

View the Mobil Delvac 1300 Super (<https://www.mobil.com/industrial/Lubricants/Product-Series/Mobil-Delvac-1300-Super>)
Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac 1300 Super 10W-30 and 15W-40 are extra high performance diesel engine oils that help extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, Mobil Delvac 1300 Super will also deliver the same exceptional performance in older conventional engines. As a result, they meet or exceed the requirements of the API CJ-4, CI-4 PLUS and CH-4 service categories as well as key Original Equipment Manufacture (OEM) requirements for 2007 engines.

Mobil Delvac 1300 Super is the result of extensive cooperative development work with major OEMs and is recommended for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries. These products will provide outstanding protection in the most demanding diesel engines of Caterpillar, Cummins, Detroit, Mack, Mercedes Benz, Navistar, Volvo, and others. Mobil Delvac 1300 Super also meets the requirements of the API SM specification for gasoline engines and mixed fleets.

Features and Benefits

As engine designs change in response to tougher emissions restrictions imposed by the EPA, the performance demand on engine lubricants likewise increases in order to compensate for the harsher environments that new engine designs bring with them. New engines (model-year 2007 and beyond) will come equipped with aftertreatment devices installed in the engine exhaust stream which will require the use of both API CJ-4 oils and ultra-low sulfur fuels to function properly. Additionally, new engines using EGR will generate even higher levels of acid, soot and heat than older EGR engines due to substantially increased EGR rates compared to previous EGR designs.

Mobil Delvac 1300 Super 10W-30 and 15W-40 are formulated with a) optimized baseoil technology containing severely hydroprocessed base stocks, b) patented Trimer* additive technology and c) a mixed detergent system to deliver cutting-edge performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and outstanding TBN retention for long drain intervals, Mobil Delvac 1300 Super's advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

* Trimer additive technology is a patented additive technology that imparts outstanding wear performance, effective oxidation resistance and improved frictional properties while contributing little to the overall ash content enabling Mobil Delvac 1300 Super to deliver performance beyond the boundaries of industry requirements of API CJ-4.

The key benefits include:

Features	Advantages and Potential Benefits
Superior soot-viscosity control	Greater engine efficiency, long engine life and long oil life
Outstanding thermal and oxidative stability	Reduced low temperature sludge build-up and high temperature deposits
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Improved corrosion protection and extended drain intervals for both new and old engines using either low (500ppm) or ultra-low (15ppm) sulfur diesel fuel
Stay-in-grade shear stability	Maintains viscosity in severe, high temperature service for greater wear protection and long engine life
Excellent low temperature pumpability	Faster oil flow and reduced wear during engine start-up in low temperatures
Superb resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket, seal, and aftertreatment (DPF and DOC) life
Meets demanding specifications of key OEMs and latest API gasoline service category	One engine oil for mixed fleet operations

Applications

- Specifically recommended for the latest low-emissions, high performance diesel applications equipped with aftertreatment systems using Diesel Particulate Filter (DPF) and Diesel Oxidation Catalyst (DOC) technologies.
- Recommended for high-performance diesel applications including turbo-charged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.
- On-highway applications operating in both high speed/high load and short haul pick-up/delivery.
- Off-highway applications operating in severe low speed/heavy load conditions using either low (500ppm) or ultra low (15ppm) sulfur fuels.
- Recommended for use in high performance gasoline engines and mixed fleet operations.
- Diesel-powered equipment from American and European OEMs.

Specifications and Approvals

Mobil Delvac 1300 Super Meets or Exceeds the requirements of:	10W-30	15W-40
API CJ-4, CI-4 PLUS, CI-4, CH-4, SM, SL	X	X
ACEA E7		X
Caterpillar ECF-3	X	X
Cummins CES 20081	X	X

Mobil Delvac 1300 Super has the following builder approvals:	10W-30	15W-40
Detroit Fluids Specification 93K218	X	X
Mack EO-O Premium Plus	X	X
MB-Approval 228.31		X
Volvo VDS-4, VDS-3, VDS-2	X	X
Allison TES-439		X

Mobil Delvac 1300 Super is recommended by ExxonMobil for applications requiring:	10W-30	15W-40
API CF	X	X
API CF-2		X

Typical Properties

Mobil Delvac 1300 Super		
SAE Grade	10W-30	15W-40
Viscosity, ASTM D 445		
cSt @ 40°C	79	114
cSt @ 100°C	11.9	15.0
CCS, cP, ASTM D 5293	6500 @ -25°C	6500 @ -20°C
MRV, cP, ASTM D 4684	27,000 @ -30°C	19,000 @ -25°C
HTHS @ 150°C, cP, ASTM D4683	3.6	4.3
Viscosity Index, ASTM D 2270	145	137
Sulfated Ash, wt%, ASTM D 874	1.0	1.0
Total Base #, mg KOH/g, ASTM D 2896	10.5	10.5
Pour Point, °C, ASTM D 97	-30	-30
Flash Point, °C, ASTM D 92	230	236

Density @ 15°C kg/l, ASTM D 4052	0.869	0.876
----------------------------------	-------	-------

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac 1300 Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com (<http://www.exxonmobil.com>)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™