

ExxonMobil > PDS Search (https://www.exxonmobil.com/pds) >

 $Mobil \ Delvac \ Super \ 1300 \ 15W40 \ PDS \ (https://www.exxonmobil.com/Commercial-Vehicle-Lube/Mobil-Delvac-Super-1300-15W40/pds-SG) \rightarrow English$ 

# Mobil Delvac Super 1300 15W-40

Mobil Commercial Vehicle Lube, Singapore

High Performance Diesel Engine Oil

# Product Description

Mobil Delvac Super 1300 15W-40 is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in on and off-highway severe service applications. Mobil Delvac Super 1300 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

#### Features and Benefits

The technology in Mobil Delvac Super 1300 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

#### **Applications**

## Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

## Specifications and Approvals

Mobil Delvac Super 1300 15W-40 has the following builder approvals:	
MB-Approval 228.1	X
MAN 271	X

Mobil Delvac Super 1300 15W-40 is also recommended by ExxonMobil for use in applications requiring:	
API CG-4/CF-4/CD/SJ	X
ACEA E2	X
Volvo VDS	X

## Typical Properties

SAE Grade	15W-40
Viscosity, ASTM D 445	

cSt @ 40°C	106
cSt @ 100°C	14.2
Viscosity Index, ASTM D 2270	136
Sulfated Ash, wt%, ASTM D 874	1.2
Total Base # , mg KOH/g, ASTM D 2896	9.0
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	220
Density @ 15°C kg/l, ASTM D 4052	0.88

#### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment

The Mobil logotype, the Pegasus design, Delvac (and any other trademarks) are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Asia Pacific Ltd 1 HarbourFront Place #06-00 HarbourFront Tower One Singapore 098633

+65 6885 8000

http://www.exxonmobil.com (http://www.exxonmobil.com)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com (http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

## Energy lives here

Select country (http://corporate.exxonmobil.com/?query=http%3a%2f%2fwww.mobil.com%2fenglish-SG%2fCommercial-Vehicle-Lube%2fpds%2fGLAPMobil-Delvac-Super-1300-15W40#global-websites)