



OUR BUSINESS IS HEAVY DUTY LUBRICANTS

Tel: (305)681-6110 Fax: (305)681-0906 / Miami, FL 33167 www.PETRO-FLORIDA.com

PRODUCT SPECIFICATIONS & TECHNICAL DATA

HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS

PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS are blended with high quality base stocks and additives to inhibit oil oxidation, protect against corrosion, and provide excellent rust and foam protection. **PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS** provide continual protection to gears during periods of high temperature operation, and are approved for MACK GO-A.

PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS are extreme pressure, heavy duty lubricants that contain a sulfur phosphorus additive package, developed to meet rigorous service demands and provide excellent gear and bearing protection. **PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS** are compatible with most other gear lubricants. Because these lubricants are multi-purpose, the worry of misapplication is minimized, and inventory control is simplified.

APPLICATIONS:

PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS are recommended for construction equipment, truck and bus fleets, farm machinery and passenger cars. They can be used for service fill, make-up, or top-off of manual transmissions, differential, rear axles, manual steering gears, final drives and universal joints.

PETROFLO BRAND HEAVY DUTY MULTI-PURPOSE GEAR LUBRICANTS and SAE 90W AND SAE 140W meets or exceeds the requirements of API Designations GL-1, and also meets Mack GO-J and Military Specification, MIL-L-2105E.

TYPICAL ANALYSIS

	<u>EP 90W</u>	<u>EP 140W</u>
Gravity API	26.5	24.1
Viscosity Index	110	110
Flash Point °F	425	450
Pour Point °F	-15	-20
Viscosity SUS @ 100° F	1175	2495
Viscosity SUS @ 210° F	96.1	150
ISO VG	220	460
AGMA	5 EP	7 EP

The above analyses are typical inspections only and the finished product may vary from batch to batch.