



OUR BUSINESS IS HEAVY DUTY LUBRICANTS

Tel: (305)681-6110 Fax: (305)681-0906 / Miami, FL 33167 www.PETRO-FLORIDA.com

PRODUCT BULLETIN **PETROFLO NON-DETERGENT OILS 10W, 20W, 30W, 40W, 50W**

PETROFLO Non-Detergent Oils are blended from select high V.I. base stocks, containing oxidations, corrosion and, anti-wear inhibitors to protect engines operating under moderate conditions.

PROPERTIES & BENEFITS:

1. Strict viscosity control, insures quality products at all times;
2. High viscosity index, promotes stable lubricating film, at various operating temperatures;
3. Low pour point, insures quick starts, under cold starting conditions;
4. Oxidations stability, inhibitor fortifies the natural stability of the oil;
5. Various grades, available in wide range of viscosity.

APPLICATION:

For light to moderate duty service.

TYPICAL ANALYSIS

	<u>10W</u>	<u>20W</u>	<u>30W</u>	<u>40W</u>	<u>50W</u>
ISO Grade	46	68	100	150	220
Gravity API	29.0	27.6	26.9	27.0	27.0
Viscosity SUS @100 F. D-87	230	335	550	850	1250
Viscosity SUS @210F D-88	49	55	70	82	101
Viscosity Index Min D 567	105	105	105	105	105
Flash COC F. Min. D-92	395	415	435	455	475
Pour Point D-97	-15	-15	-4	+5	+14

The above analyses are typical inspections only and the finished product may vary from batch to batch.