

# FormulaShell™

## BRAKE FLUID

### FormulaShell™ BRAKE FLUID DOT-3 AUTOMATIC TRANSMISSION FLUID

---

#### Product Description

**FormulaShell™ BRAKE FLUID DOT-3** is a glycol-based hydraulic brake fluid which meets Department of Transportation (DOT 3) requirements for automotive hydraulic brake fluid as well as Motor Vehicle Brake Fluid Standard SAE J-1703. **FormulaShell™ BRAKE FLUID DOT-3** formulated for use with disc and drum brakes, foreign and domestic cars, trucks, buses and motorcycles where a DOT 3 fluid is specified. **FormulaShell™ BRAKE FLUID DOT-3** contains oxidation and corrosion inhibitors, which provide excellent corrosion protection for the metallic components of the brake system. **FormulaShell™ BRAKE FLUID DOT-3** also resists oxidation from the high temperatures encountered in modern disc braking systems. Follow vehicle manufacturer's recommendation when adding brake fluid.

#### APPLICATIONS

Recommended for use in the hydraulic brake system of any motor vehicles where:

- DOT 3 hydraulic brake fluid requirements are specified
- Brake Fluid Standard SAE J-1703 requirements are specified
- Motor Vehicle Safety Standards No. 116 requirements are specified

**FormulaShell™ BRAKE FLUID DOT-3** is not a silicone-based brake fluid and does not meet DOT 4 or DOT 5 brake fluid requirements. **FormulaShell™ BRAKE FLUID DOT-3** should never be used in place of or mixed with silicone-based brake fluid, nor should it be used where DOT 4 or DOT 5 fluid is specified.

All brake fluids should be kept clean and dry; dirt or water contamination could cause brake system failure.

#### FEATURES

- Meets or exceeds Federal Motor Vehicle Safety Standard (FMVSS) No. 516.116, ISO-4925, and SAE-J1703
- Minimum dry boiling point exceeds 450°F (232°C)
- Minimum wet boiling point 284°F (140°C)
- Excellent compatibility with elastomeric system components
- Resistance to oxidation and corrosion
- High-Temperature stability
- Low-temperature fluidity

#### HANDLING & SAFETY INFORMATION

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.