



SHELL SPIRAX[®] LS

Premium limited-slip differential gear oil

Product Description

Shell Spirax[®] LS oil is a premium high performance multigrade extreme-pressure, multipurpose automotive gear lubricant specifically formulated for use in passenger cars and light-duty trucks with limited-slip differentials. It meets the requirements of API GL-5 and is available in SAE viscosity grade 80W-90.

Applications

- initial fill, complete refill, and service fill of all passenger car and light-duty truck conventional and limited-slip differentials
- conventional manual transmissions calling for API GL-5

Features/Benefits

- conventional and limited-slip differential capabilities protect hypoid gears against wear and scuffing
- outstanding thermal stability for cleanliness and promotes longer service life
- multi-viscosity for year round use over wide temperature range
- compatible with other automotive gear oils

Approvals and Recommendations

- meets the requirements for passenger car and light truck limited-slip differentials.
- API Service GL-5

Typical Properties of Shell Spirax[®] LS

	Test Method	80W-90
		Product Code
Gravity, °API	D 1298	25.6
Viscosity:		
@ 40°C, cSt	D 445	135
@ 100°C, cSt	D 445	14.5
Viscosity Index	D 270	106
Flash Point, COC, °F	D 92	425
Pour Point, °F	D 97	-10

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>