



OUR BUSINESS IS HEAVY DUTY LUBRICANTS

Tel: (305)681-6110 Fax: (305)681-0906 / Miami, FL 33167 www.PETRO-FLORIDA.com

PRODUCT BULLETIN **PETROFLO XO 25W-50 DIESEL ENGINE OIL**

PetroFlo XO 25W-50 is a natural high viscosity index, super performance diesel engine oil that provides excellent protection for diesel engines operating in severe service applications. **PetroFlo XO 25W-50** is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries. **PetroFlo XO 25W-50** delivers high performance in both naturally aspirated as well as turbo-charged diesel powered equipment in European, Japanese, and American manufacturers.

Features / Benefits

- High viscosity shear stability
- Excellent Fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Thermal and oxidation stability
- Advanced varnish, sludge protection and prolonged engine life
- Excellent detergency/dispersancy

Typical Properties **PetroFlo XO 25W-50 Diesel Engine Oil**

Specific Gravity @ 60°F	0.88
Density, lbs/gal @ 60°F	7.34
Color, ASTM D1500	L 4.0
Flash Point °C	235
Pour Point, °C	-25
Viscosity, Kinematic	
cSt @ 40°C	210
cSt @ 100°C	20.0
Viscosity Index	115
Sulfated Ash, ASTM D874, wt %	0.9
Total Base Number (TBN), ASTM D2896	9.0

Typical properties are average values only. Minor variations that do not affect product performance are to be expected during normal manufacture, at different blending locations. Product formulations are subject to change without notification.